

SAX & DOM

CPS 116

Introduction to Database Systems

Announcements (Thu. Oct. 27)

- ❖ Homework #3 due in 1 week
- ❖ Project milestone #2 due in 2 weeks

SAX & DOM

- ❖ Both are API's for XML processing
- ❖ SAX (Simple API for XML)
 - Started out as a Java API, but now exists for other languages too
- ❖ DOM (Document Object Model)
 - Language-neutral API with implementations in Java, C++, etc.
- ❖ JAXP (Java API for XML Processing)
 - Bundled with standard JDK
 - Includes SAX, DOM parsers and XSLT transformers

SAX processing model

❖ Serial access

- XML document is processed as a stream
- Only one look at the data
- Cannot go back to an early portion of the document

❖ Event-driven

- A parser generates events as it goes through the document (e.g., start of the document, end of an element, etc.)
- Application defines event handlers that get invoked when events are generated

SAX events

Most frequently used events:

- ❖ **startDocument** <?xml version="1.0"?> → startDocument
- ❖ **endDocument** <bibliography> → startElement
- ❖ **startElement** <book ISBN="ISBN-10" price="80.00"> → startElement
 <title>Foundations of Databases</title>
 ... → startElement
- ❖ **endElement** </book> → endElement characters endElement
- ❖ **characters** </bibliography> → endElement
 ... → endDocument
 - Whenever the parser has processed a chunk of character data (without generating other kinds of events) Whitespace may come up as **characters** or **ignorableWhitespace**, depending on whether a DTD is present
 - Warning: The parser may generate multiple **characters** events for one piece of text

A simple SAX example

❖ Print out text contents of **title** elements

```
import java.io.*;  
import org.xml.sax.*;  
import org.xml.sax.helpers.XMLReaderFactory;  
import org.xml.sax.helpers.DefaultHandler;  
  
public class SaxExample extends DefaultHandler {  
    public static void main(String[] argv) throws Exception {  
        String fileName = argv[0];  
        // Create a SAX parser:  
        XMLReader xr = XMLReaderFactory.createXMLReader();  
        // Parse the document with this event handler:  
        xr.setContentHandler(new SaxExample());  
        xr.parse(new InputSource(new FileReader(fileName)));  
        return;  
    }  
    ...  
}
```

A simple SAX example (cont'd)

```
7
private StringBuffer titleStringBuffer = null;    Only relevant when
public void startElement(String uri, String localName, ↑
Assuming no namespace, String qName,           namespace is involved
processing, qName is tag name      Attributes attributes) {
    if (qName.equals("title"))
        titleStringBuffer = new StringBuffer();
}
public void endElement(String uri, String localName,
String qName) {
    if (qName.equals("title")) {
        System.out.println(titleStringBuffer.toString());
        titleStringBuffer = null;
    }
}
public void characters(char[] ch, int start, int length) {
    if (titleStringBuffer != null)
        titleStringBuffer.append(ch, start, length);
}
Warning: This code does not handle data with //title[//title] pattern
```

A common mistake

What is wrong with the following?

```
8
private String titleString = null;
public void endElement(String uri, String localName,
String qName) {
    // Print the last chunk of characters seen before </title>:
    if (qName.equals("title"))
        System.out.println(titleString);
}
public void characters(char[] ch, int start, int length) {
    titleString = new String(ch, start, length);
}
```

- ❖ Cannot handle the case where other tags appear within a `title` element
- ❖ It is possible that `characters()` are called multiple times for one piece of text; this code only prints out the last part

A more complex SAX example

- 9
- ❖ Print out the text contents of top-level section titles in books, i.e., `//book/section/title`
 - Old code would print out all titles, e.g., `//book/title`, `//book//section/title`
 - For simplicity, assume that if we have the pattern `//book/section/title//book/section/title`, we print the higher-level `title` element
 - ❖ Idea: maintain as state the path from the root

```
private ArrayList path = new ArrayList();
private int pathLengthWhenOutputIsActivated;
```

A more complex SAX example (cont'd)¹⁰

```
public void startElement(String uri, String localName,
                        String qName,
                        Attributes attributes) {
    path.add(qName); // Maintain the path.
    if (path.size() >= 3 &&
        ((String)(path.get(path.size()-1))).equals("title") &&
        ((String)(path.get(path.size()-2))).equals("section") &&
        ((String)(path.get(path.size()-3))).equals("book")) {
        // path matches //book/section/title:
        if (titleStringBuffer == null) {
            pathLengthWhenOutputIsActivated = path.size();
            titleStringBuffer = new StringBuffer();
        }
    }
}
```

A more complex SAX example (cont'd)¹¹

```
public void endElement(String uri, String localName,
                      String qName) {
    if (titleStringBuffer != null &&
        path.size() == pathLengthWhenOutputIsActivated) {
        // Closing the element that activated output buffering:
        System.out.println(titleStringBuffer.toString());
        titleStringBuffer = null;
    }
    path.remove(path.size()-1); // Maintain the path.
}
public void characters(char[] ch, int start, int length) {
    if (titleStringBuffer != null)
        titleStringBuffer.append(ch, start, length);
}

This check prevents premature output
in case that title has subelements
Would it work if we change this check to qName.equals("title")?
```

DOM processing model¹²

- ❖ XML is parsed by a parser and converted into an in-memory DOM tree
- ❖ DOM API allows an application to
 - Construct a DOM tree from an XML document
 - Traverse and read a DOM tree
 - Construct a new, empty DOM tree from scratch
 - Modify an existing DOM tree
 - Copy subtrees from one DOM tree to another etc.


DOM Node's

13

- ❖ A DOM tree is made up of Node's
- ❖ Most frequently used types of Node's:
 - **Document**: root of the DOM tree
 - Not the same as the root element of XML
 - **DocumentType**: corresponds to the DOCTYPE declaration in an XML document
 - **Element**: corresponds to an XML element
 - **Attr**: corresponds to an attribute of an XML element
 - **Text**: corresponds to chunk of text

DOM example

14



Node interface

15

- n.getNodeType() returns the type of Node n
 - n.getChildNodes() returns a NodeList containing Node n's children
 - For example, subelements are children of an Element; DocumentType is a child of the Document
 - d.getDocumentElement() returns the root Element of Document d
 - e.getTagName() returns the tag name of Element e
 - e.getAttributes() returns a NamedNodeMap (hash table) containing the attributes of Element e
 - Attributes are not considered children!
 - a.getNodeName() returns the name of Attr a
 - a.getNodeValue() returns the value of Attr a
 - t.getNodeValue() returns the content of Text t
- For convenience: n.getParentNode(), n.getPreviousSibling(), n.getNextSibling(), n.getOwnerDocument(), etc.

Constructing DOM from XML

16

```
import java.io.*;
import javax.xml.parsers.*;
import org.xml.sax.*;
import org.w3c.dom.*;
import javax.xml.transform.*;
import javax.xml.transform.dom.*;
import javax.xml.transform.stream.*;

public class DomExample {
    public static void main(String[] args) throws Exception {
        // Parse input XML into a DOM Document:
        DocumentBuilderFactory factory=DocumentBuilderFactory.newInstance();
        DocumentBuilder builder=factory.newDocumentBuilder();
        Document document=builder.parse(new File(args[0]));
        // Use the default (identity) Transformer to print the DOM Document:
        TransformerFactory tFactory=TransformerFactory.newInstance();
        Transformer transformer=tFactory.newTransformer();
        transformer.transform(new DOMSource(document),
                             new StreamResult(System.out));
    }
}
```

In general, you can use an XSLT Transformer instead

Traversing DOM

17

❖ Compute the string value of an XML node

```
public static String convertNodeToString(Node n) {
    // String value of a Text Node is just its content:
    if (n.getNodeType() == Node.TEXT_NODE)
        return n.getNodeValue();
    // String value of a Node of another type is the concatenation
    // of its children's string values:
    String text = "";
    NodeList children = n.getChildNodes();
    for (int i=0; i<children.getLength(); i++) {
        Node child = children.item(i);
        text = text + convertNodeToString(child);
    }
    return text;
}
```

Traversing DOM (cont'd)

18

❖ Print out text contents of title elements

```
public static void outputTitle(Node n) {
    if (n.getNodeType() == Node.ELEMENT_NODE &&
        n.getnodeName().equals("title")) {
        // This is a title Element; output it:
        System.out.println(convertNodeToString(n));
    } else {
        // Recurse down the tree and look for titles to output:
        NodeList children = n.getChildNodes();
        for (int i=0; i<children.getLength(); i++) {
            Node child = children.item(i);
            outputTitle(child);
        }
    }
}
```

❖ How would you print out just //book/section/title?

- Use getParentNode() to check for section parent and book grandparent

Constructing DOM from scratch

19

- ❖ Construct a DOM Document showing all titles as follows:

```
<result>
<title text="title1"/>
<title text="title2"/>...
</result>

public static Document newDocWithTitles(Document inputDoc)
throws Exception {
    // Create a new Document:
    DocumentBuilderFactory factory=DocumentBuilderFactory.newInstance();
    DocumentBuilder builder=factory.newDocumentBuilder();
    Document newDoc=builder.newDocument();
    // Create the root Element:
    Element newElement=newDoc.createElement("result");
    newDoc.appendChild(newElement);
    // Add titles:
    addTitlesToNewDoc(newDoc, inputDoc);
    return newDoc;
}
```

Constructing DOM from scratch (cont'd)

20

```
public static void addTitlesToNewDoc(Document newDoc, Node n)
throws Exception {
    if (n.getNodeType() == Node.ELEMENT_NODE &&
        n.getnodeName().equals("title")) { You can only create an Element
        // This is a title Element; add it: within a Document
        Element newElement = newDoc.createElement("title");
        newElement.setAttribute("text", convertNodeToString(n));
        newDoc.getDocumentElement().appendChild(newElement);
    } else {
        // Recurse down the tree and look for titles to add:
        NodeList children = n.getChildNodes();
        for (int i=0; i<children.getLength(); i++) {
            Node child = children.item(i);
            addTitlesToNewDoc(newDoc, child);
        }
    }
}
```

Copying subtrees in DOM

21

- ❖ Construct a DOM Document showing all title elements from the input XML

```
public static Document newDocWithTitles2(Document inputDoc)
throws Exception {
    ...
    // Add titles:
    addTitlesToNewDoc2(newDoc, inputDoc);
    ...
}

public static void addTitlesToNewDoc2(Document newDoc, Node n)
throws Exception {
    if (n.getNodeType() == Node.ELEMENT_NODE &&
        n.getnodeName().equals("title")) {
        Node newNode = newDoc.importNode(n, true);
        newDoc.getDocumentElement().appendChild(newNode);
    } else {
        ...
    }
}
```

A Document can import (copy) a Node from another element
The second argument specifies whether to copy recursively or not

Summary: SAX versus DOM

22

❖ SAX

- Because of one-pass processing, a SAX parser is fast, consumes very little memory
- Applications are responsible for keeping necessary state in memory, and are therefore more difficult to code

❖ DOM

- Because the input XML needs to be converted to an in-memory DOM-tree representation, a DOM parser consumes more memory
 - Lazy materialization of DOM tree helps alleviate this problem
- Applications are easier to develop because of the powerful DOM interface

❖ Which one scales better for huge XML input?
